Working Paper

Applications of System Identification and Parameter Estimation in Water Quality Modeling

M. B. Beck

September 1979
WP-79-99

International Institute for Applied Systems Analysis
A-2361 Laxenburg, Austria

Applications of System Identification and Parameter Estimation in Water Quality Modeling

M. B. Beck

September 1979
WP-79-99

M.B. BECK is a research scientist at the International Institute for Applied Systems Analysis, Schloss Laxenburg, 2361 Laxenburg, Austria.

PREFACE

In recent years there has been a considerable interest in the development of models for river and lake ecological systems. Much of this interest has been directed towards the development of progressively larger and more complex simulation models. In contrast, relatively little attention has been devoted to the problems of uncertainty and errors in the field data, of inadequate numbers of field data, of uncertainty in the relationships between the important system variables, and of uncertainty in the model parameter estimates. IIASA's Resources and Environment Area's Task on "Models for Environmental Quality Control and Management" addresses problems such as these.

A brief summary of the literature on applications of system identification and parameter estimation in water quality modeling is provided in this paper. The paper is therefore concerned with summarizing the status of current and recent studies in water quality model calibration.

SUMMARY

Applications of techniques of system identification and parameter estimation in water quality modeling are surveyed. This survey of the literature covers three areas: river water quality, lake water quality, and wastewater treatment plant modeling. The applications cited are classified according to the type of algorithm used for calibration, the type of model, and the field data used. Two broad distinctions are made between: (a) off-line and recursive methods of parameter estimation; and (b) internally descriptive (state-space) and black box (input/output) model types. In order to assist the classification, a number of estimation algorithms are very briefly introduced. Although there are clearly different lines of development in each area of water quality modeling, it is possible to identify problems common to all three areas. The major problems discussed concern the availability of field data, levels of noise in the data, and model structure identification.

1. INTRODUCTION

Calibration of models for water quality in rivers, lakes, and wastewater treatment processes is, in several important respects, different from the problem of calibrating, for example, rainfall-runoff and flood-routing models. Records of water quality data are often restrictively short and inadequate for the purposes of time-series analysis; the data are subject to particularly high levels of error; the system to be described is rarely of the multiple-input/single output form (a form which permits substantial simplification of the anlysis); and significant input perturbation of the system behaviour, such as the storm event, is often absent from the recorded data. Indeed, relationships between "causes" and "effects" are not always self-evident prior to the analysis of the field data. One may argue, therefore, that applying techniques of system identification and parameter estimation to problems of water quality modeling is not to be treated as a straight-forward extension of the approaches typically used in the analysis of other forms of hydrological modeling.

This paper surveys the literature of water quality model calibration. Since the applications cited are classified according to the type of parameter estimation algorithm used, the following section introduces a minimum of explanation for a number of potentially applicable algorithms. Section 3 is the principal component of the survey. It is not an exhaustive review; space restrictions do not allow more than just a brief survey of the literature. Section 4 deals with the salient

problems of current applications of parameter estimation algorithms in water quality modeling.

2. ESTIMATION ALGORITHMS

Many algorithms are available for parameter estimation, although the majority of these algorithms are not substantially different from the basic notion of a least squares estimator. Certainly, the fundamental role of least squares as the point of departure in developing more complex algorithms is undisputed (Draper and Smith, 1966; Eykhoff, 1974; Gelb, 1974; Young, 1974; Kashyap and Rao, 1976; Graupe, 1976).

Let us define, therefore, the following criterion function for model parameter estimation (or calibration) as,

$$J \triangleq \sum \underset{\sim}{\varepsilon}^T(\hat{\underset{\sim}{\alpha}})\underset{\sim}{\underset{\sim}{W}}\underset{\sim}{\varepsilon}(\hat{\underset{\sim}{\alpha}}) \qquad (1)$$

in which $\hat{\underset{\sim}{\alpha}}$ is a vector of model parameter estimates and $\underset{\sim}{\varepsilon}$ is a vector of errors between model-based estimates of the system responses and field observations of those responses. $\underset{\sim}{\underset{\sim}{W}}$ is a matrix of weighting coefficients, various choices for which define different estimation algorithms. When $\underset{\sim}{\underset{\sim}{W}} = \underset{\sim}{\underset{\sim}{I}}$, the identity matrix, minimization of (1) with respect to $\hat{\underset{\sim}{\alpha}}$ yields the least squares estimates. In most cases of practical interest, the least squares estimates will be biased because, in general, the noise (or random error) sequences assumed to be present in the observed field data do not conform to white noise sequences. Thus, it cannot be assumed that the least squares estimates will equal the supposedly "true" values of the system parameters. One of the most widely used algorithms that avoids this problem is the method of maximum likelihood (see, for example, Åström

and Bohlin, 1966; Box and Jenkins, 1970). Maximum likelihood estimation is equivalent to the substitution $\underset{\sim}{W} = \underset{\sim}{R}^{-1}$ in the criterion function (1), where $\underset{\sim}{R}$ is either the covariance maxtrix of the output response measurement errors (Gelb, 1974) or the computed covariance matrix of the errors $\underset{\sim}{\varepsilon}$ (Källström et al., 1976). Assumptions about the statistical properties of the noise sequences (their mean and covariance) are necessary in order to make this substitution. If, in addition, it is assumed that each element of the noise sequence vector is independent of all other elements, then a somewhat simpler estimator results. Under this assumption, $\underset{\sim}{W}$ is a diagonal matrix and the estimator is frequently referred to as weighted least squares.

An instrumental variable estimator (Kendall and Stuart, 1961; Johnston, 1963; Young, 1976) also avoids the problem of biased estimates. The method seeks to generate a sequence of variables with specific statistical properties -- the instrumental variables -- that may be substituted into an essentially least-squares-like algorithm. For certain forms of the instrumental variable estimator (e.g., Young, 1974), the instrumental variables are virtually equivalent to state estimates. There are, therefore, strong similarities between this estimator and the extended Kalman filter (Jazwinski, 1970), an algorithm that treats the problem of parameter estimation as a problem of combined state-parameter estimation. In that sense the method of quasilinearization is similar to the extended Kalman filter since it too sets up the parameter estimation problem by interpreting the model parameters as additional system state variables (Bellman and Kalaba, 1965; Lee, 1968).

Many of the above and closely related algorithms can be implemented as either off-line or recursive schemes of parameter estimation. The basic difference between the two schemes is that an off-line scheme assumes that a single, fixed set of estimates $\hat{\underset{\sim}{\alpha}}$ may be substituted for computation of the response errors ($\underset{\sim}{\varepsilon}$) for all N field observations sampled from time $t_1 \rightarrow t_N$. With a recursive scheme it is possible to compute estimates $\hat{\underset{\sim}{\alpha}}(t_k)$ for each kth instant of time, and therefore it is possible to estimate time-varying parameter values.

3. SURVEY OF APPLICATIONS

Table 1 gives a broad survey of the literature on applications of parameter estimation to water quality modeling in streams, lakes, and wastewater treatment plants. Classification according to the type of model used is chosen partly because it is instructive to judge the size of the model being calibrated, and partly because the choice of model (internally descriptive, or black box) defines, to some extent, the nature of an appropriate estimation algorithm. Unless otherwise indicated, as either a "regression" or "black box" model, all the models referenced in Table 1 are internally descriptive models. By "internally descriptive" it is meant that the model is derived from existing theory and that it attempts to describe those internal chemical, biological, and physical mechanisms which are thought to govern system behaviour.

A few remarks are necessary in order to qualify the contents of Table 1. For example, the paper by Ivakhnenko et al. (1977) is primarily concerned with the problems of model discrimination and model structure identification (see below)

as opposed to the problem of parameter estimation (which the GMDH algorithm treats by least squares estimation). Other references, Shastry et al. (1973), Beck and Young (1976), Beck (1976), Jolankai and Szöllösi-Nagy (1978), and Halfon et al. (1979) are similarly oriented towards the analysis of identifying model structure.

The literature quoted for stream and lake water quality modeling shows a predominant bias towards the use of internally descriptive models, whereas the papers addressing wastewater treatment plant models tend to exhibit the opposite bias towards the use of black box time-series models. This reflects, in the latter case, a somewhat "retarded" development of model calibration exercises in wastewater treatment plant modeling. For stream water quality modeling Table 1 in fact reflects a rather selective survey of the literature. There have been several applications of frequency response, correlation analysis, and time-series analysis techniques in stream quality modeling, for example, Thomann (1967, 1973), Fuller and Tsokos (1971), Edwards and Thornes (1973), Schurr and Ruchti (1975), and Mehta et al. (1975). Further applications of time-series analysis in wastewater treatment plant modeling can be found in Berthouex et al. (1975, 1976).

4. SALIENT PROBLEMS

It is apparent from the previous section (and Table 1) that model calibration has developed differently in the three chosen areas of water quality modeling. This is partly a consequence of different objectives for the use of models. However, similarities of the problems experienced in each area are more pronounced than their differences. Thus three

general problems are discussed: (a) availability of field data; (b) noise levels in the data; and (c) degree of a priori knowledge.

Availability of field data. An essential difference between, for example, the calibration of rainfall-runoff and flood-routing models and the calibration of water quality models is that data for the latter have usually been sampled not only at inadequately low frequencies but also for insufficient continuous periods of time. It is a characteristic feature of lake and biological wastewater treatment systems that they exhibit relatively fast and relatively slow components of dynamic behaviour, both of which are important for obtaining a model of the system. A lake ecological model calibrated against short-term records, under the inevitable assumption that longer-term dynamic properties are essentially at steady-state, would clearly be inappropriate for making forecasts of long-term behaviour patterns. Two recent developments, one of an analytical nature and one related to instrumentation hardware, may significantly alter the situation regarding availability of data. First, Spear and Hornberger (1978), in their analysis of a lake eutrophication problem, propose that even patchy, inadequate field data and qualitative observations permit a meaningful calibration exercise; logical constraints on acceptable model performance, rather than a squared error function such as equation (1), provide the criterion for calibration. Second, improvements in specific-ion electrodes and the installation of telemetry networks for water quality monitoring will radically alter the quantity and kind of field data available for analysis.

Noise levels in the data. This problem is probably most emphasized in data collected from routine operations at wastewater treatment plants. The lack of well identified "deterministic" input disturbances, such as the storm event, leads to field data with apparently low signal/noise ratios. Consequently, it is difficult to estimate accurate input/output relationships and thus time-series models will tend preferentially to identify autoregressive properties of the output observations sequence. There is, therefore, very little natural experimental basis for system identification. Moreover, extreme events in ecological systems, for instance, the sudden phytoplankton bloom, occur because a specific but relatively commonplace combination of environmental conditions force the state of the system into a region in which a nonlinear mode of behaviour is excited. Such significant variation of the responses is rarely related to extreme input disturbances.

Degree of a priori knowledge. A typical feature of water quality modeling is that the analyst is often uncertain of the basic cause-effect relationships in the system under investigation. And even when he knows these relationships it is not always clear what form they should take. Model structure identification is the problem of resolving such issues by reference to experimental field data (Beck, 1978, 1979a). More precisely, model structure identification may be defined as the problem of identifying the way in which the input disturbances are related to the state variables, how the states are related among themselves, and how in turn the measured output responses are related to the state variables. Solution of this problem naturally precedes accurate estimation of the

model parameter values, although the solution may itself depend upon the application of an estimation algorithm. If one accepts that the issue of model structure identification is of major importance -- and the literature does not suggest a widespread recognition thereof -- then it is reasonable to argue that calibration of water quality models should concentrate on establishing that which is essentially "deterministic" about the observed system behaviour. It is, in fact, premature to focus attention on detailed assumptions about the distributions and correlation properties of the random components of the system's behaviour.

5. CONCLUSIONS

The calibration of water quality models is still at a primitive stage of development. These conclusions summarize the status of applying parameter estimation techniques to the three areas of lake water quality, wastewater treatment plant, and river quality modeling.

(a) A desire to characterize all the detailed features of a lake ecological system has led to the development of particularly complex internally descriptive models of such systems. These models have little likelihood of being rigorously calibrated against field data; indeed, their level of theoretical complexity seems disproportionately high when compared with the severely restricted range of available field data.

(b) In contrast, the objectives of quantifying and controlling the variability of wastewater treatment plant behaviour have led typically to the calibration of low-order black box models for these systems. Such models, however, yield little insight into the dominant (microbiological) mechanisms that

govern the dynamics of waste removal processes.

(c) For stream quality modeling there has been a more balanced progress in both black box and internally descriptive approaches to model construction and its associated calibration problems. With present techniques and data it would be possible to calibrate a dynamic lumped-parameter model that accounts for the basic properties of day-to-day variations in DO-BOD interaction, phytoplankton growth, and nitrification in rivers.

REFERENCES

Adayemi, S.O., Wu, S.M., and Berthouex, P.M. (1979) Modeling and control of a phosphorus removal process by multivariate time series method. Water Research vol. 13, 105-112.

Åström, K.J. and Bohlin, T. (1966) Numerical identification of linear dynamic systems from normal operating records. In Theory of Self-adaptive Control Systems (edited by P. H. Hammond): Plenum, New York, USA. pp. 96-111.

Beck, M.B. (1975) The identification of algal population dynamics in a nontidal stream. In Computer Simulation of Water Resources Systems (edited by G. C. Vansteenkiste): North-Holland, Amsterdam, Holland. pp. 483-494.

Beck, M.B. (1976) An analysis of gas production dynamics in the anaerobic digestion process. Technical report no. CUED/F-CAMS/TR135, University Engineering Department, Cambridge, England.

Beck, M.B. (1978) Random signal analysis in an environmental sciences problem. Applied Mathematical Modeling, vol. 2, no. 1, 23-29.

Beck, M.B. (1979a) Model structure identification from experimental data. In Theoretical Systems Ecology (edited by E. Halfon): Academic, New York, USA. pp. 259-289.

Beck, M.B. (1979b) On-line estimation of nitrification dynamics. Professional paper no. PP-79-3, International Institute for Applied Systems Analysis, Laxenburg, Austria.

Beck, M.B. and Young, P.C. (1976) Systematic identification of DO-BOD model structure. Proc. Am. Soc. Civ. Engrs., J. Env. Eng. Div., vol. 102, no. EE5, 909-927.

Bellman, R.E. and Kalaba, R.E. (1965) Quasilinearization and nonlinear boundary-value problems: American Elsevier, New York, USA.

Benson, M. (1979) Parameter fitting in dynamic models. Ecological Modeling, vol. 6, 97-115.

Berthouex, P.M., Hunter, W.G., Pallesen, L.C. and Shih, C-Y. (1975) Modeling sewage treatment plant input BOD data. Proc. Am. Soc. Civil Engnrs., vol. 101, no. EE1, 127-138.

Berthouex, P.M., Hunter, W.G., Pallesen, L.C. and Shih, C-Y. (1976) The use of stochastic models in the interpretation of historical data from sewage treatment plants. Water Research, vol. 10, 689-698.

Berthouex, P.M., Hunter, W.G., Pallesen, L.C. and Shih, C-Y. (1978) Dynamic behaviour of an activated sludge plant. Water Research, vol. 12, no. 11, 957-972.

Bowles, D.S. and Grenney, W.J. (1978a) Steady-state river quality modeling by sequential extended Kalman filters. Water Resources Res., vol. 14, 84-95.

Bowles, D.S. and Grenney, W.J. (1978b) Estimation of diffuse loading of water quality pollutants by Kalman filtering. In Applications of Kalman Filter to Hydrology, Hydraulics and Water Resources (edited by C-L. Chiu): University of Pittsburgh, Stochastic Hydraulics Program, Pittsburgh, USA. pp. 581-597.

Box, G.E.P. and Jenkins, G.M. (1970) Time-series analysis, forecasting and control: Holden-Day, San Francisco, USA.

Crowther, J.M., Dalrymple, J.F., Woodhead, T., Coackley, P., and Hamilton, I.M. (1976) The application of statistical modeling to wastewater treatment. In Systems and Models in Air and Water Pollution (Proceedings of a Symposium, London, September, 1976): Institute of Measurement and Control, London, U.K.

Di Cola, G., Guerri, L., and Verheyden, H. (1976) Parameter estimation in a compartmental aquatic ecosystem. In Identification and System Parameter Estimation (Preprints IVth IFAC Symposium, Tbilisi, USSR, September, 1976): Institute of Control Sciences, Moscow, USSR, Part 2, pp. 157-165.

Di Toro, D.M. and van Straten, G. (1979) Uncertainty in the parameters and predictions of phytoplankton models. Working paper no. WP-79-27, International Institute for Applied Systems Analysis, Laxenburg, Austria.

Draper, N.R. and Smith, H. (1966) Applied regression analysis: Wiley, New York, USA.

Edwards, A.M.C. and Thornes, J.B. (1973) Annual cycle in river water quality: a time-series approach. Water Resources Res., vol. 9, 1286-1295.

Erni, P.E. and Ruchti, J. (1977) Der Sauerstoffhaushalt von Fliessgewaessern: kritische Pruefung eines mathematischen Sauerstoffmodells Anhand der Identifikation seiner Parameter in Flussen und kuenstlichen Rinnen. Schweiz Z. Hydrol., vol. 39, no. 2, 261-276.

Eykhoff, P. (1974) System identification -- parameter and state estimation: Wiley, Chichester, U.K.

Fuller, F.C. and Tsokos, C.P. (1971) Time-series analysis of water pollution data. Biometrics, vol. 27, 1017-1034.

Gelb, A. (Ed.) (1974) Applied optimal estimation: M.I.T. Press, Cambridge, USA.

Gnauck, A., Wernstedt, J., and Winkler, W. (1976) On the use of real-time estimation methods for the mathematical modeling of limnological ecosystems. In Identification and System Parameter Estimation (Preprints, IVth IFAC Symposium, Tbilisi, USSR, September, 1976): Institute of Control Sciences, Moscow, USSR, Part 2, pp. 124-133.

Graupe, D. (1976) Identification of Systems: Robert E. Krieger Publishing Co., Huntington, New York, USA.

Halfon, E., Unbehauen, H., and Schmid, C. (1979) Model order estimation and system identification theory and application to the modeling of ^{32}P kinetics within the trophogenic zone of a small lake. Ecological Modeling, vol. 6, 1-22.

Huck, P.M. and Farquhar, G.T. (1974) Water quality models using the Box-Jenkins method. Proc. Am. Soc. Civ. Engrs., J. Env. Eng. Div., vol.100, no. EE3, 733-752.

Ivakhnenko, A.G., Krotov, G.I., Cheberkus, V.I. and Vysotskiy, V.N. (1977) Identification of dynamic equations of a complex plant on the basis of experimental data using self-organization of models, Part 1 - one dimensional problems. Soviet Automatic Control, vol. 10, no. 2, 24-30.

Jazwinski, A.H. (1970) Stochastic processes and filtering theory: Academic, New York, USA.

Johnston, J. (1963) Econometric methods: McGraw-Hill, New York, USA.

Jolankai, G., and Szöllösi-Nagy, A. (1978) A simple eutrophication model for the bay of Keszthely, Lake Balaton. In Modeling the Water Quality of the Hydrological Cycle (Proceedings of the Baden Symposium, September, 1978), pp. 137-150: IAHS Publ. no. 125.

Källström, C.G., Essebo, T., and Åström, K.J. (1976) A computer program for maximum likelihood identification of linear multivariable stochastic systems. In Identification and System Parameter Estimation (Preprints, IVth IFAC Symposium, Tbilisi, USSR, September, 1976): Institute of Control Sciences, Moscow, USSR, pp. 508-521.

Kashyap, R.L., and Rao, A.R. (1976) Dynamic stochastic models from empirical data: Academic Press, New York, USA.

Kendall, M.G. and Stuart, A. (1961) Advanced theory of statistics: Griffin, London, U.K.

Koivo, A.J. and Phillips, G.R. (1971) Identification of mathematical models for DO and BOD concentration in polluted streams from noise corrupted measurements. Water Resources Res., vol. 7, no. 4, 853-862.

Koivo, A.J. and Phillips, G.R. (1972) On determination of BOD and parameters in polluted stream models from DO measurements only. Water Resources Res., vol. 8, no. 2, 478-486.

Koivo, A.J. and Phillips, G. R. (1976) Optimal estimation of DO, BOD and stream parameters using a dynamic discrete time model. Water Resources Res. vol 12, no. 4, 705-711.

Koivo, H.N. and Koivo, A.J. (1978) Least-squares estimator for polluted stream variables in a distributed parameter model. Advances in Water Resources, vol. 1, 191-194.

Lee, E.S. (1968) Quasilinearization and invariant embedding: Academic Press, New York, USA.

Lee, E.S. and Hwang, I. (1971) Stream quality modeling by quasilinearization. J. Wat. Pollut. Contr. Fedn., vol. 43, no. 2, 306-317.

Lettenmaier, D.P. and Burges, S.J. (1976) Use of state estimation techniques in water resource system modeling. Wat. Resources Bulletin, vol. 12, no. 1, 83-99.

Lewis, S. and Nir, A. (1978) A study of parameter estimation procedures of a model for lake phosphorus dynamics. Ecological Modeling, vol. 4, 99-117.

Marsili-Libelli, S. (1979) Reduced-order modeling of activated sludge process. (submitted to Ecological Modeling).

Mehta, B.M., Ahlert, R.C. and Yu, S.L. (1975) Stochastic variation of water quality in the Passaic Rivers. Water Resources Research, vol. 11, no. 2, 300-308.

Moore, R.J. and Jones, D.A. (1978) Coupled Bayesian-Kalman filter estimation of parameters and states of dynamic water quality models. In Applications of Kalman Filter to Hydrology, Hydraulics and Water Resources (edited by C-L. Chiu): University of Pittsburgh, Stochastic Hydraulics Program, Pittsburgh, USA., pp. 599-635.

Olsson, G. and Hansson, O. (1976) Modeling and identification of an activated sludge process. In Identification and System Parameter Estimation (Preprints, IVth IFAC Symposium, Tbilisi, USSR, September, 1976): Institute of Control Sciences, Moscow, USSR, pp. 134-146.

Rinaldi, S., Soncini-Sessa, R., Stehfest, H. and Tamura, H. (1979) Modeling and control of river quality: McGraw-Hill, New York, USA.

Schurr, J.M. and Ruchti, J. (1975) Kinetics of oxygen exchange, photosynthesis and respiration in rivers determined from time-delayed correlations between sunlight and dissolved oxygen. Schweiz. Z. Hydrologie, vol, 37, no. 1, 144-174.

Shastry, J.S., Fan L.T. and Erickson, L.E. (1973) Non-linear parameter estimation in water quality modeling. Proc. Am. Soc. Civ. Engrs., J. Env. Eng. Div., vol. 99, no. EE3, 315-331.

Spear, R.C. and Hornberger, G.M. (1978) Eutrophication in Peel Inlet. Report No. AS-R19, Centre for Resource and Environmental Studies, Australian National University, Canberra, Australia.

Stehfest, H. (1978) On the monetary value of an ecological river quality model. Research report no. RR-78-1, International Institute for Applied Systems Analysis, Laxenburg, Austria.

Svrcek, W.Y., Elliott, R.F., and Zajic, J.E. (1974) The extended Kalman filter applied to a continuous culture model. Biotechnology and Bioengineering, vol. XVI, 827-846.

Tamura, H. (1978) On some identification techniques for modeling river quality dynamics with distributed lags. In Handbook of Large-Scale Systems Engineering Applications (edited by M.G. Singh and A. Titli): North-Holland, Amsterdam, Holland (in press).

Thé, G. (1978) Parameter identification in a model for the conductivity of a river based on noisy measurements at two locations. In Modeling, Identification and Control in Environmental Systems (edited by G. C. Vansteenkiste): North-Holland, Amsterdam, Holland, pp. 823-839.

Thomann, R.V. (1967) Time-series analysis of water quality data. Proc. Am. Soc. Civ. Engrs., J. Sanit. Eng. Div., vol. 93, no. SA1, 1-23.

Thomann, R. V. (1973) Effect of longitudinal dispersion on dynamic water quality response of streams and reservoirs. Water Resources Research, vol. 9, no. 2, 355-366.

Whitehead, P.G. and Young, P.C. (1975) A dynamic-stochastic model for water quality in part of the Bedford Ouse river system. In Computer Simulation of Water Resources Systems (edited by G. C. Vansteenkiste): North-Holland, Amsterdam, Holland, pp. 417-438.

Young, P.C. (1974) A recursive approach to time-series analysis. Bulletin Institute of Mathematics and its Applications, vol. 10, 209-224.

Young, P.C. (1976) Some observations on instrumental variable methods of time-series analysis. Int. J. Control, vol. 23, 593-612.

Young, P.C. and Whitehead, P.G. (1977) A recursive approach to time-series analysis for multivariable systems. Int. J. Control, vol. 25, 457-482.

TABLE 1. Summary of Recent Applications of Parameter Estimation Algorithms in Water Quality Modeling

Author(s)	Field Data	Algorithm	Type of Model
STREAM WATER QUALITY MODELING			
Koivo & Phillips (1971)	--	Stochastic Approximation (Least Squares); R*	Time & space; BOD, DO; analytical solution to 1st-order partial differential equation.
Koivo & Phillips (1972)	--	Least Squares; O+	Space; BOD, DO; steady-state analytical solution to 1st-order partial differential equation.
Koivo & Phillips (1976)	--	Linear Kalman filter; R	Time & space; BOD, DO; difference equations
Koivo & Koivo (1978)	--	Least Squares (state estimation only); R	Time & space; BOD, DO; 1st-order partial differential equation.
Lee & Hwang (1971)		Quasilineralization (Least Squares); O	Space; BOD, DO; ordinary differential equation.
Shastry et al. (1973)	Sacramento River (1962)	Weighted Least Squares; Maximum Likelihood; O	Space; BOD, DO; ordinary differential equation.
Huck & Farquhar (1974)	St. Clair River (1971)	Maximum Likelihood; O	Single point spatial location, time-variations; DO, chloride; black box, time-series model.
Beck (1975)	River Cam (1972)	Maximum Likelihood; O	Time; BOD, DO; ordinary differential equation; also black box time-series model
Beck & Young (1976)	River Cam (1972)	Extended Kalman Filter; R	Time; BOD, DO; ordinary differential equation.
Whitehead & Young (1975)	Bedford-Ouse River (1973)	Multivariable Instrumental Variable-Approximate Maximum Likelihood (MIVAML); R	Time; BOD, DO; difference equations
Young & Whitehead (1977)	River Cam (1972) Bedford-Ouse River (1973)	MIVAML; R	Time; BOD, DO; difference equations
Lettenmaier and Burges (1976)	--	Extended Kalman Filter; R	Space; BOD, DO; ordinary differential equations
Erni & Ruchti (1977)	Aare River	Differential Approximation Method; O	Single point spatial location; time-variations; DO; difference equations.
Ivakhnenko et al. (1977)	River Cam (1972)	Group Method of Data Handling (GMDH); O	Single point spatial location; time variations; BOD, DO; difference equations.

TABLE 1. (Continued)

Author(s)	Field Data	Algorithm	Type of Model
Stehfest (1978)	Rhine River (1971)	Quasilinearization (Least Squares); O	Space; BOD, DO; ordinary differential equations
Stehfest (1978)	Rhine River (1971)	Quasilinearization (Least Squares); O	Space; easily degradable organic matter, slowly degradable organic matter, bacterial mass, protozoan mass, DO; ordinary differential equations.
Bowles & Grenney (1978a)	Jordan River, Utah	Extended Kalman Filter; R	Space; BOD, DO, NH_3-N, NO_3-N, algal-N, organic-N; ordinary differential equations.
Moore & Jones (1978)	River Cam (1972)	Coupled Bayesian-Kalman Filter; R	Time; BOD, DO; ordinary differential equations.
Rinaldi, et al. (1979)	Bormida River	Least Squares; O	Space; BOD, DO; analytical solution to 1st-order ordinary differential equations.
Tamura (1978)	--	Linear Kalman Filter (and others); R	Time & space; BOD, DO; difference equations.
Thé (1978)	River Rhine	Linear Kalman Filter; R	Time and space; conductivity; 2nd-order partial differential equation (finite difference approximation solution).
	LAKE WATER QUALITY MODELING		
Di Cola et al. (1976)	Leopold's Park Pond, Brussels (1973-75)	Least Squares; O (solved as an optimal control problem)	Time: autotrophs, herbivores, carnivores; ordinary differential equations.
Gnauck et al. (1976)	Saidenbach Reservoir, GDR (1966-70); Klicava Reservoir, CSSR (1963-72)	Least Squares; R	Time; DO, chlorophyll-a, particulate organic matter; regression relationship.
Jolankai and Szöllösi-Nagy (1978)	Lake Balaton, Hungary (1971-77)	Maximum Lakelihood; R	Time; soluble reactive phosphorus, chlorophyll-a, exchangeable phosphorus in sediment; ordinary differential equations.
Lewis and Nir (1978)	Greifensee, Switzerland (1973)	Weighted Least Squares; O	Time; soluble reactive phsphorus, particulate phosphorus; ordinary differential equations.
Halfon, et al. (1979)	Small lake ecosystem	Least Squares (also frequency domain analysis); O	Time; soluble phosphorus, particulate phosphorus, a low molecular weight form of phosphorus, colloidal phosphorus; ordinary differential equations.

TABLE 1. (Continued)

Author(s)	Field Data	Algorithm	Type of Model
Benson (1979)	Lake Placid, British Columbia, Canada	Least Squares; O	Time; phytoplankton biomass; ordinary differential equation.
Di Toro and van Straten (1979)	Lake Ontario (1972)	Weighted Least Squares; O	Time; 16 state variables divided between epilimnion and hypolimnion layers; ordinary differential equations.
WASTEWATER TREATMENT PLANT MODELING			
Svrcek, et al. (1974)	--	Extended Kalman Filter; R	Time; cell and substrate concentrations (general continuous culture process); ordinary differential equations
Olsson and Hansson (1976)	Kaeppala Works Stockholm	Maximum Likelihood; O	Time; DO (activated sludge unit); black box, time-series model.
Crowther, et al. (1976)	Philipshill Works, Scotland	Maximum Likelihood; O	Time; BOD, suspended solids (primary sedimentation tanks); black box, time-series model.
Beck (1976)	Norwich Works, England	Instrumental Variable; R	Time; gas production rate (anaerobic digestion unit); black box, time-series model.
Berthouex, et al. (1978)	Madison Works, Wisconsin	Maximum Likelihood; O	Time; BOD (activated sludge unit); black box, time-series model.
Adayemi, et al. (1979)	Jones Island Works, Milwaukee Wisconsin	Maximum Likelihood; O	Time; total soluble phosphorus (phosphorus precipitation unit); black box, time-series model.
Beck (1979b)	Norwich Works, England	Extended Kalman Filter; R	Time: NH_3-N, NO_3-N, Nitrosomonas, Nitrobacter (activated sludge unit); ordinary differential equations.
Marsili-Libelli (1979)	Pilot plant, Florence, Italy	Least Squares (with cubic splines smoothing); O	Time; BOD, bacterial concentration (activated sludge unit); ordinary differential equations.

FOOTNOTES:

* R denotes a recursive estimation algorithm

† O denotes an off-line estimation algorithm