1 Cross-sectoral implications of the implementation of irrigation water use

2 efficiency policies in Spain: A nexus footprint approach

3 Barbara A. Willaarts,^{1,2}* Yolanda Lechón,³ Beatriz Mayor,^{1,2} Cristina de la Rúa,³ Alberto Garrido^{2,4}

4 ¹International Institute of Applied System Analysis (IIASA), Laxenburg, Austria

² Water Observatory-Botin Foundation, Madrid, Spain

6 ³Centro de Investigaciones Energéticas, Medioambientales y Tecnológicas (CIEMAT), Madrid, Spain

⁷ ⁴Research Center for the Management of Environmental and Agricultural Risks (CEIGRAM), Universidad Politécnica

8 de Madrid, Spain

9 *Corresponding author email: <u>willaart@iiasa.ac.at</u>; Address: Schlossplatz 1A, 2361 Laxenburg, Austria

10

11 Abstract

One technical solution often suggested for alleviating water scarcity is to increase the efficiency of 12 irrigation water use. In Spain, several plans have been launched since 2000 to upgrade irrigation 13 infrastructures and thereby achieve water savings equivalent to 2,500 hm³/year and promote rural 14 15 development. The present study uses a footprint approach to evaluate the impacts on land, water, energy, and carbon emissions of the implementation of irrigation modernization policies in 16 agriculture in Spain between 2005 and 2011. The results show that during the period studied, the 17 irrigated area remained stable (+0.3%), although there was a shift in crop patterns, with low-value 18 non-permanent crops being replaced by high-value permanent crops. The water demand for 19 irrigation decreased by 21%; half of this is explained by the shift in crop patterns and the reduction 20 of the consumptive fraction (i.e., blue water footprint), and the other half by the cutback of return 21 flows associated with the higher efficiency of the irrigation infrastructure. Changes in water demand 22 have been accompanied by a progressive substitution of surface water for groundwater. Reduced 23 water demand for irrigation has brought a reduction of 13% in water's energy footprint and 21% in 24 its carbon footprint. In relative terms, water efficiency (m³ consumed/m³ irrigated) has increased by 25 8%, although this has also increased the energy intensity (kWh/m^3) to 9%. The emission rate 26 (KgCO₂ equiv./m³ irrigated) has decreased by 12% as a result of the drop in the emission factor of 27 electricity production. Overall, irrigation modernization policies in Spain have supported the 28 transition from an irrigation sector that is less technified and heavily dependent on surface water into 29 30 one that is more productive and groundwater-based. From a resource-use perspective, such transition has contributed to stabilizing or even decreasing the irrigated land, and surpass the annual water 31 savings target of 2,500 hm³, although it has also made the sector more energy-dependent. Despite the 32 overall positive outcomes, the observed water savings are masked by various synergistic factors, 33

including favorable climatological conditions toward the end of the study period, which contributed
strongly to curbing overall irrigation water demand. In the light of the higher frequency of observed
droughts in Spain, the investments done so far do not guarantee that the planned water saving targets
can be sustained if not complemented with additional measures like restricting irrigated area and/or
setting caps for water intensive crops.

Keywords: water footprint, energy footprint, carbon footprint, irrigation modernization, water
scarcity, water-energy-food nexus, groundwater, surface water

41

42 Introduction

Water demand is increasing worldwide as a result of multiple drivers linked to urbanization,
globalization, climate change, economic development and population growth (Cosgrove and Loucks,
2015; Hoekstra and Mekonnen, 2012; Mehram et al., 2017; Veldkamp et al., 2017; WWPA, 2016).
As the most important global user of water (FAO, 2016; Gleick et al., 2014) agriculture lies at the
core of many water disputes throughout the world (Llamas and Martínez-Santos, 2005; Molden et
al., 2007). This is particularly true in arid and semi-arid regions, where the share of consumptive
water use by irrigation easily reaches 90% (Hoekstra and Mekonnen, 2012).

In many arid and semi-arid regions, water scarcity is not just a growing environmental concern but 50 also a structural problem (Berbel et al., 2015). During much of the 20th century, the prevailing 51 approach to tackling water scarcity relied on the promotion of supply-oriented approaches, also 52 53 called "hard-path" solutions (i.e., building infrastructures to secure availability) (Gleick, 2003). 54 While this water management strategy has greatly contributed to improving water security in many 55 regions, water demands have continued to rise, with many water systems approaching their physical 56 boundaries. The need for a paradigm shift has promoted the development of so-called soft-path solutions or demand-driven approaches, and the focus is now on improving resource-use efficiency 57 and strengthening water governance (Gleick, 2003; OECD, 2011). 58

From the resource management perspective, increasing water use efficiency is seen as a key strategy in terms of meeting current and future development needs, while at the same time reducing pressure on the environment (Dumont et al., 2013). Large investments have been devoted to this purpose, particularly in agriculture, to improve the "crop per drop." However, the outcomes of water efficiency policies have not always led to net water savings (Grafton et al., 2018; Pfeiffer and Lin, 2014, Scheierling et al., 2006; Ward and Pulido-Vazquez, 2008), and have often generated

unaccounted-for costs and impacts (Diaz et al., 2012). Spain is a paradigmatic case, being the most 65 66 semi-arid country and the largest water consumer within the European Union (EUROSTAT, 2014). Irrigated agriculture in Spain accounts for 75% of national water consumption and is at the core of 67 many regional water disputes (De Stefano and Llamas, 2012). Over the last decades, several policy 68 measures have been implemented to ameliorate water scarcity and stress. The Spanish National 69 Irrigation Plan (MAPA 2001a) and later the Shock Plan (2006–2008) (MARM 2006) are probably 70 71 the most ambitious public initiatives implemented to date. The plans' overall purpose was to upgrade approximately 2.0 million ha of irrigated land, thereby saving 2,500 hm³ of water annually, while 72 73 strengthening the resilience and competitiveness of the Spanish agricultural sector (Lopez-Gunn et al., 2012). Despite there being no official ex post evaluation of this process, several studies were 74 75 carried out in different basins to assess their outcomes in terms of water use and agricultural productivity. Dumont et al. (2013), Lecina et al. (2010), and Playan et al. (2006) confirmed the trend 76 77 observed in other countries and regions for the Ebro basin in northeast Spain. They showed that although net agricultural water use did not reduce after the modernization process—and even slightly 78 79 increased—the transformed areas saw significant increases in land productivity. As Dumont et al. (2013) described, increasing agricultural water use efficiency from a technical perspective might 80 81 unintentionally lead to an overall aggregated increase in water consumption instead of the opposite, 82 namely, the so-called rebound effect. This phenomenon, further explained and translated into numbers by Gómez and Gutiérrez (2011) and Gómez and Pérez-Blanco (2014), was also reported in 83 the Guadalquivir basin (Berbel et al., 2013) and the Mediterranean region (Lorite et al., 2004). 84

The upgrading of irrigation infrastructures in Spain has been subsidized by public funds, but farmers 85 also had to bear about 50% of the costs. To obtain returns on their investments, farmers might use 86 the initial water "savings" to irrigate larger areas, and/or assume greater risks (i.e., by cultivating 87 more profitable and more water-intensive crops or by intensifying crop rotations). All these decisions 88 may offset any potential savings, and, at worst, increase overall water consumption at the basin 89 scale. Berbel et al. (2015) showed that such a rebound effect in southern Spain was avoided to a 90 91 large extent due to additional policy measures, including strict regulations limiting the expansion of irrigated land area. Likewise, water allocations were also revised in such a way that the water 92 93 savings obtained were not reassigned to any economic use but returned into the system to improve 94 the water balance and the environmental status of surface and groundwater bodies.

In addition to contested evaluations about actual net water savings, several authors have reported that
increasing water use efficiency also has other unintended consequences like greater energy use

97 (Corominas, 2010; Rodriguez-Diaz et al., 2012; Soto-Garcia et al., 2013) and often a larger carbon
98 footprint (Daccache et al., 2014).

99 Despite growing evidence on the trade-offs associated with increasing water use efficiency, much of

the available literature on Spain either provides very context-specific examples or addresses the

101 water-energy-food-carbon nexus on an almost bilateral basis, for example, water-energy and/or

102 water-food links (e.g., Kuriqi et al., 2017, 2019; Martinez-Paz et al., 2018).

Accordingly, this paper aims to provide a comprehensive assessment of the implications linked to the modernization of irrigated infrastructures in Spain at national level from a resource-use perspective, including the use of water, land, energy, and carbon emissions. While this assessment is country-specific, the approach is transposable. The results are expected to contribute to the ongoing debate on the synergies and trade-offs linked to the promotion of technical measures to improve agricultural water use efficiency.

109 Methods

110 A footprint approach was applied to quantify the trends in water and energy consumption and carbon emissions linked to agricultural irrigation development in Spain. The temporal scale of analysis 111 comprises the period 2005–2011, and the spatial unit of analysis are the administrative boundaries 112 equivalent to provinces (NUTS3 in the nomenclature of territorial units for statistics within the EU) 113 and the Autonomous Communities (NUTS2). The analysis focuses on irrigated croplands in the open 114 air. Irrigated areas in greenhouses were excluded, as these are already considered as modernized 115 irrigated areas and the margin for improving resource-use efficiency for this type of agriculture is 116 limited. A summary of the methodological approach is presented in Figure 1, and a detailed 117 description of the data and modeling approach is presented below. 118



119



121 **2.1 Water footprint**

To quantify the annual consumptive use of water for irrigation we used the water footprint (*WF*) accounting methodology developed by Hoektra et al. (2011) and refined for the specific case of Spain by Garrido et al. (2011). The *WF* is here understood as the consumptive fraction of green (soil moisture) and blue water (surface and/or groundwater irrigation) embedded in the production of an agricultural crop. Accordingly, the annual *WF* of irrigated agriculture was estimated taking into account the total amount of green and blue water that is evapotranspired in year *i* by all open air irrigated areas.

129
$$WF_i(hm^3) = \sum_{j=1}^{49} \sum_{z=1}^{50} \left(WF_{green \, j, z} + WF_{blue \, j, z} \right)$$
 (1)

where WF_{green} (hm³) represents the annual green water footprint of crop *j* and NUTS3 z and WF_{blue} (hm³) is the annual blue water footprint. The *WF* analysis in this study was limited to the 49 most important irrigated crops in the open air (equivalent to 90% of the irrigated area in Spain in 2011) according to MAGRAMA (2015a).

The annual WF_{green} of a crop *j* in a NUTS3 *z* equals the sum of the monthly (*g*) effective precipitation (*P_{eff}*) during its cultivation period when the crop water requirements (*CWR*) are not met.

136
$$WF_{green\,i,j,z} (hm^3) = \sum_{g=1}^n \min(CWR_{j,z,g}; P_{eff\,z,g}) \times S_{irr\,i,j,z} \times 10^{-5}$$

(2)

- where S_{irr} (ha) is the irrigated area in year *i* and was obtained from the Yearly Agricultural Statistics of the Spanish Ministry of Agriculture (MAGRAMA, 2015a).
- 140 P_{eff} depends on the monthly precipitation (*p*) and was calculated using the formulae proposed by
- 141 Brouwer and Heibloem (1986).

142
$$P_{effz,g}$$
 (mm) = 0.8 × p_g - 25, *if* p_g > 75 mm (3)

143
$$P_{effz,g}$$
 (mm) = $0.6 \times p_g - 10$, if $p_g < 75$ mm

144 *CWR* was estimated based on the reference evapotranspiration (ET_o) in month g and NUTS3 z, and 145 the crop coefficient (K_c), which is the ratio of water requirements along the different growth stages.

146
$$CWR_{j,z,g}(mm) = \sum_{g=1}^{n} ET_{o\,z,g} \times K_{c\,j,g}$$
 (4)

147 Monthly values of p and ET_o (mm) were obtained from 50 meteorological stations (one per NUTS3)

of the Spanish National Agency of Meteorology (AEMET, 2015) for the time series October 2005

until September 2011, and estimated using the approach by Penman-Monteith (Allen et al., 2006).

- 150 Planting and harvesting dates were obtained from MAPA (2001b) and assumed to remain constant
- throughout the years. Appendix A summarizes the K_c values for the different growing stages (initial,
- development, mid-season, and end), and the planting and harvesting dates for the 49 irrigated cropsunder consideration.

The annual WF_{blue} was estimated as the sum of the volume of water needed when $CWR > P_{eff}$ during the cultivation period of crop *j* in NUTS3 *z*.

156
$$WF_{blue\,i,j,z} (hm^3) = \sum_{g=1}^n \max(0; CWR_{j,z,g} - P_{eff\,z,g}) \times S_{irr\,i,j,z} \times 10^{-5}$$
 (5)

The blue groundwater footprint ($WF_{blue GW}$) was estimated based on the annual groundwater use ratios (*ratio* $_{GW}$) obtained from the annual survey of agricultural water use for the period 2005–2011 (INE, 2012). As these ratios are provided at administrative units equivalent to NUTS2, it was assumed that in year *i* all crops cultivated in the different NUTS3 belonging to the same NUT2 (*k*) have the same *ratio* $_{GW}$. Appendix B summarizes the annual ratios of surface and groundwater use per NUTS2.

163
$$WF_{blue\,GW\,i,i}\,(hm^3) = \sum_{k=1}^{17} WF_{blue\,i,j,z} \times ratio_{GW\,k,i}$$
(6)

164
$$WF_{blue SW i,j} (hm^3) = \sum_{k=1}^{17} WF_{blue i,j,z} \times (1 - ratio_{GWk,i})$$
 (7)

165 **2.2 Energy footprint**

- 166 The energy footprint (EF_i) computes the energy use associated with surface (EF_{SWi}) and groundwater
- 167 (EF_{GWi}) irrigation along two steps: 1) withdrawal and pumping from the source (i.e. off-farm), and
- 168 2) irrigation within the plot (i.e. on-farm). Electricity was considered as the main source of energy,
- 169 which is a reasonable assumption, as most irrigated systems in Spain have become almost
- 170 completely dependent upon electricity (Corominas, 2010).

171
$$EF_{i} (GWh) = \sum_{j=1}^{49} \sum_{z=1}^{50} (EF_{SWi} + EF_{GWi}) = \sum_{j=1}^{49} \sum_{z=1}^{50} [Irr_{SWi,z,j} \times (q_{pump_{SW}i,z} + q_{plot}i,z) + Irr_{GWi,z,j} \times (q_{pump_{GW}i,z} + q_{plot}i,z)]$$
(8)

- where Irr (hm³) is the amount of water demand for irrigation, either from surface water (Irr_{SW}) or
- 174 groundwater (Irr_{GW}), q_{pump} (kWh/m³) is the average energy consumption from pumping and
- transportation of water i.e. off-farm energy cost and dependent on the source of water, and q_{plot}
- (kWh/m^3) is the energy demand for irrigation on-farm, and which depends only on the irrigation
- technology.

178 Irr was estimated based on the WF_{blue} by applying a loss coefficient equivalent to the inverse of the irrigation scheme's efficiency (*Eff*). Irrigation efficiency was estimated separately for surface (*Eff*_{SW}) 179 and groundwater (*Eff*_{GW}), as a product of pumping and transportation efficiencies and plot irrigation 180 efficiencies. Pumping and channel distribution efficiencies for each type of irrigation scheme were 181 obtained as a mean of the average values reported by the River Basin Management Plans of the 182 largest Spanish River basins, including the Ebro, Duero, and Guadalquivir (CHD, 2015; CHE, 2015; 183 CHG, 2015). Plot irrigation efficiencies were estimated per year and NUTS3 as a weighted average 184 of the irrigation efficiencies and area coverage per system σ (i.e., drip, sprinkling, automotive, and 185 gravity). Appendix C provides a summary of the estimated efficiency values. 186

187
$$Irr_{SWi}(hm^3) = WF_{blue\,SWi}/Eff_{SW}$$
(9)

188
$$Irr_{GWi}(hm^3) = WF_{blue GWi}/Eff_{GW}$$
 (10)

189 Where $WF_{blue SW}$ represents the volume of surface water from the total WF_{blue} and the $WF_{blue GW}$ 190 equals the groundwater fraction. The annual return flows (RF_i) represent the irrigated water volume 191 that is not evapotranspired and returns to the system.

$$192 \quad RF_i(hm^3) = (Irr_{SWi}-WF_{blue SWi}) + (Irr_{GWi}-WF_{blue GWi}) \tag{11}$$

193 q_{plot} was calculated taking into account the relative energy consumption (ω , kWh/m³) of each 194 irrigation system σ and the area ratio (S_{σ}) each system occupies per NUTS3 and year. S_{σ} was obtained from the annual crop surveys (MAGRAMA, 2015b) and included in Appendix B. Table 1

196 summarizes the ω values used in the analysis.

197
$$q_{plot \, i,z} \left(kWh/m^3 \right) = \sum_{\sigma=1}^n \omega_{plot \, \sigma} \times S_{\sigma,z,i} \tag{12}$$

Table 1. Mean energy consumption (ω, kWh/m³) per irrigation system in Spain. Source: Corominas (2010)

Irrigation system	$\omega_{plot \sigma}$	$\omega_{pump \sigma}$	
Gravity	0	0.02	
Sprinkler and automotive	0.24	0.05	
Drip	0.18	0.10	

200 $q_{pump \text{ SW}}$ was estimated as a weighted average of the mean energy use linked to surface water 201 pumping and transportation per irrigation system σ and the annual S_{σ} .

202
$$q_{pump SW i,z} \left(kWh/m^3 \right) = \sum_{\sigma=1}^n \omega_{pump \sigma} \times S_{\sigma,z}$$
(13)

where ω_{pump} is the average energy consumption (kWh/m³) associated with water withdrawal and transportation for an irrigation system σ (see Table 1).

- $q_{pump GW}$ was calculated based on the energy requirement to lift the water and following the method
- and assumptions proposed by Karimi et al. (2012). According to these authors, and based on Nelson
- and Robertson (2008), lifting 1000 m^3 water for 1 m at 100% efficiency, without considering friction

losses requires 2.73 kWh. Accordingly, $q_{pump GW}$ we estimated as:

209
$$q_{pumpGWi,z} (kWh/m^3) = (2.73 \times D_{i,z}/(Eff_{pump} \times (1 - TI) \times 1000)$$
 (14)

- where 2.73 represents unitary cost per meter depth (kWh/m), D is average pumping depth (m) per
- NUTS3 z and year *i*, Eff_{pump} is pump efficiency (%), and *TI* are pump transmission and distribution
- losses (%). *Eff_{pump}* was assumed to be 90% and TI losses established at 20%. Data on D was obtained

from the official water bodies' qualitative state monitoring network (MAGRAMA, 2015c) and refers

to the average annual water table depth per NUTS3. See Appendix D.

215 **2.3 Carbon footprint**

The carbon footprint (*CF*) calculates the emissions of greenhouse gases (GHGs) linked to the use of electricity for irrigating crops. Emissions linked to the building of the new irrigation infrastructures have not been considered, as they are regarded as negligible (Abrahao et al., 2017).

219
$$CF_i \ (kg \ CO_2 \ equiv) = \sum_{j=1}^{49} \sum_{z=1}^{50} (EF_{SWi} + EF_{GWi}) \ x \ GHG_{mix \ i}$$
(15)

where GHG_{mix} , (kg CO₂ equiv./kWh) in year *i* is the greenhouse gas emission factor of the electricity production mix, and EF_{SW} and EF_{GW} are expressed in kWh. GHG_{mix} are calculated considering the composition of the electricity generation mix of technologies per year according to the following expression:

- 224 $GHG_{mix\,i}(kg\,CO_2\,equiv./kWh) = \sum_{1}^{n} ELCTECH_{i,x} \times GHG_{i,x}$ (16)
- where $ELCTECH_{i,x}$ is the percentage contribution of each power generation technology x and GHG_i 225 is the individual GHG emission rate of each technology in year *i*. ELCTECH_{*i*,*x*} values were obtained 226 227 from the annual reports of Spanish Electric Network (REE, 2006, 2012), the electricity production and transport system operator in Spain. Life Cycle Assessment (LCA) methodology was used to 228 229 estimate the Carbon Footprint of each individual power technology contributing to the electricity generation mix. The Ecoinvent database (Frischknecht et al., 2005) was the source of the processes 230 used to model each technology, with the general Ecoinvent datasets being adapted to the specific 231 conditions of the Spanish mix. The Life Cycle Assessment software Simapro, a product of PRé 232 Consultants (https://simapro.com/), was used to model the mix and estimate the aggregated GHG 233 emissions. These emissions included the aggregated life cycle GHG emissions along the fuel chain 234 and the emissions produced in the upstream (raw material extraction and production of components) 235 and downstream stages (waste management). *GHG_{mix,i}* values are summarized in Table 2. 236

Table 2. Evolution of the GHG emission factor of electricity production in Spain, 2005–2011
 period. Source: own calculations.

Year	GHG emission rate GHG _{mix}	
	(kg CO ₂ equiv./kWh)	
2005	0.457	
2006	0.475	
2007	0.481	
2008	0.422	
2009	0.382	
2010	0.298	
2011	0.398	

240 **2.4 Characterization of Spanish irrigated systems**

239

241 We performed a multivariate analysis to understand the variability of irrigated crops across the

territory, the temporal changes in the different crop footprints, and their correlation with a number of

243 descriptive variables (see Appendix E). Specifically, we applied a factorial analysis (FA) using the

244 Statistical Software XLSTAT 2017.4.45380 to reduce the dimensionality of the original matrix (24

variables x 56 observations corresponding to the 8 most irrigated $NUTS2^{1}$ for each of the 7 years) to

¹ These 8 administrative units embrace 94% of the national irrigated area in both 2005 and 2011

- a reduced number of factors or gradients that can explain the observed temporal and spatial
- 247 variability of irrigated crops within Spain.

248 **Results**

- Figure 2 summarizes the annual evolution of the *WF*, *EF*, and *CF* of irrigated crops between 2005
- and 2011. Despite the relative stability of the irrigated area (2.85 million ha in 2005 and 2.86 million
- ha in 2011), the WF over the entire period decreased by 13.0% (17,134 hm³ in 2005 to 14,903 hm³ in
- 252 2011) (Figure 2a). The *WF* blue SW is the most important component of the total *WF*, but has
- decreased by 22.9% (12,784 hm³ in 2005 to 9,855 hm³ in 2011). This sharp decrease has been partly
- offset by a 7.0% rise in the WF _{blue GW} (3,248 hm³ in 2005 to 3,477 hm³ in 2011) and by a 42.7%
- increase in the WF_{green} (1,101 hm³ in 2005 to 1,572 hm³ in 2011). The return flows also decreased by
- 256 26.6% (10,100 hm³ in 2005 to 7,410 hm³ in 2011).
- 257 The net reduction in the use and consumption of blue water for irrigation contributed to the 13.3%
- decrease in the *EF* (7,213 GWh in 2005 to 6,253 GWh in 2011) (Figure 2b). The *EF*_{SW} component
- decreased by 16.1% (3,913 GWh in 2005 to 3,282 GWh in 2011). Nevertheless, the unitary costs of
- pumping and irrigation on farm with surface water ($q_{pump SW}$ and $q_{plot SW}$) increased by 15% (0.18)
- 261 KWh/m³ in 2005 to 0.21 KWh/m³ in 2011) (Table 3).



262

Figure 2. Annual water (a), energy (b), and carbon (c) footprints of Spanish irrigated agriculture.

The EF_{GW} reduced by 10.0% (3,300 GWh in 2005 to 2,971 GWh in 2011). The rise of the water table (Figure 2b) contributed to lowering the unitary groundwater pumping costs ($q_{pump GW}$) (Table 3), despite the overall increase in groundwater use. $q_{pump GW}$ accounted for up to 75% of the total energy costs linked to groundwater irrigation in 2011, and during the period analyzed, this variable

reduced by 3.9%.

270 Table 3. Average unitary energy consumption associated with off-farm pumping and

271 transportation (q_{pump}) , and on-farm distribution and application (q_{plot}) stages for both surface

272 and groundwater irrigation.

	Surface water			Groundwater		
	$q_{pump} (kWh/m^3)$	$q_{plot} (kWh/m^3)$	q pump (% total)	$q_{pump} (kWh/m^3)$	$q_{plot} (kWh/m^3)$	q pump (% total)
2005	0.06	0.12	31.9	0.59	0.15	78.9
2006	0.06	0.12	32.3	0.62	0.15	79.2
2007	0.06	0.13	32.1	0.56	0.16	78.8
2008	0.06	0.13	32.6	0.57	0.16	77.9
2009	0.06	0.13	32.7	0.58	0.16	78.1
2010	0.06	0.13	32.7	0.56	0.16	77.4
2011	0.07	0.14	32.3	0.48	0.16	75.0

273 The evolution of the *CF* also follows a downward trend (Figure 2c). Between 2005 and 2011, the *CF*

decreased by 24.9%, (3,295 million kg (Mkg) of CO₂ equiv. in 2005 and 2,486 Mkg CO₂ equiv. in

275 2011). These emissions represent 0.8% of the total GHG emissions inventory for Spain, as reported

by the Spanish Ministry for Agriculture and Fishing, Food, and Environment under the United

277 Nations Framework Convention on Climate Change (MAPAMA, 2017). The cutback of the CF is

due to the decrease of both fractions: the CF_{sw} decreased by 27%, while the CF_{gw} decreased by

279 21.6%.

Figure 3 shows how the *WF*, the *EF*, and the *CF* split among the different crop groups, and the

changes between 2005 and 2011. Overall, crop groups belonging to the same typology (i.e., non-

permanent and permanent crops) showed comparable footprint dynamics.²

From a water perspective, the largest share of the WF_{blueSW} in the two reference years was allocated

- to the cultivation of non-permanent crops, particularly cereals and industrial and fodder crops
- (Figure 3a). Over time, however, the WF_{blueSW} of non-permanent crops decreased overall by 48.2%
- (equivalent to an absolute reduction of $-2,894 \text{ hm}^3$). On the other hand, the WF_{blueSW} of permanent
- crops remained stable between 2005 and 2011, with a net reduction of 0.9% (equivalent to -35 hm³).

² Non-permanent crops here include cereals, industrial, fodder, vegetables, and tubers; permanent crops refer to citrus and non-citrus trees, olive trees, and vineyards.

- 288 The largest share of the WF_{blueGW} , also relates to non-permanent crops. However, the aggregated
- 289 WF_{blueGW} for non-permanents crops decreased by 11.8% (equivalent to -223 hm^3). This reduction is
- particularly due to the decrease in the WF_{blueGW} of cereals, and to a lesser extent, vegetables and
- fodder crops. On the other hand, the WF_{blueGW} of permanent crops raised overall by 28.5%
- 292 (equivalent to a net increase of +452 hm³), particularly because of the increased cultivation and
- 293 irrigation of olive and citrus trees.
- The largest fraction of return flows during the two reference years corresponds to RF_{SW} , and to a lesser extent to RF_{GW} (Figure 3a). Over time, the RF_{GW} remained stable, while the RF_{SW} decreased by 30% between 2005 and 2011.
- 297 The shifts in crop patterns and sources of water for irrigation also led to changes in the crops' *EF*
- 298 (Figure 3b). The decrease in the irrigation of non-permanent crops translated into a 35.7% reduction
- of its EF_{BlueSW} (equivalent to -617 GWh), and a 39.8% decline in its EF_{BlueGW} (equivalent to -526
- 300 GWh). This downward trend is linked to the decreasing irrigation of cereals, industrial crops, and
- 301 vegetables, and consequently of its surface and groundwater *EFs*.
- The growing cultivation and irrigation of woody permanent crops with groundwater led to a 12.0% increase in its EF_{GW} (equivalent to +197 GWh). This increase is mainly due to the rise in the EF_{GW} of olive and citrus trees.
- The CF follows a similar trend to that of the EF, although in the CF case a generalized decrease is 305 observed for all crops and sources of water (Figure 3c). The CF_{SW} and CF_{GW} of non-permanent crops 306 exhibits the largest changes, with a net reduction of 54.4% (equivalent to -395 million kg CO₂ 307 equiv.), and 50.5% (equivalent to -306 million kg CO₂ equiv.). These sharp decreases are linked to 308 the reduction of the CF_{SW} of cereals and industrial crops and, similarly, to the decline of the CF_{GW} of 309 310 cereals and vegetables. With respect to the permanent crops, the CF_{SW} also decreased overall by 16.0% (equivalent to -99 million kg CO₂ equiv.), mainly as a result of non-citrus fruit and olive 311 312 trees. The CF_{GW} of permanent crops remained stable with a net negative change equivalent to <1%.



315

Tubers

Vineyards

Legumes

134/236 22/40

113/65 109/263

36/56



Figure 3. Surface and groundwater (a) blue water footprint (hm³), (b) energy footprint (GWh),

and (c) carbon footprint (million kg CO₂ equiv.) of the main irrigated crops in Spain in 2005 (left) and 2011 (right).

Alongside with the net changes in water, energy and emissions reduction, in the relative efficiencies 320 have also experienced remarkable changes (Table 4). From a water perspective, the efficiency of 321 irrigated agriculture has improved by 7.6%. However, the increase in water use efficiency has made 322 the irrigation systems more energy-dependent, increasing the relative energy costs by 9.2%. From an 323 emissions perspective, the emission rate follows the evolution of the emission intensity of the 324 electricity production mix. This intensity increases, initially driven by an increasing penetration of 325 combined cycle natural gas (with very high associated CH₄ emissions); it starts to decrease 326 afterwards due to the penetration of renewable energies. The observed increment in the last period is 327 due to the domestic coal promotion policy initiated in 2010. Overall, there was a reduction of 11.7% 328 329 between the beginning and the end of the period analyzed.

	Water efficiency (m ³ consumed /m ³ irrigated)	Energy consumption (kWh/m ³ irrigated)	Emission rate (kg CO2 equiv./m ³ irrigated)
2005	0.61	0.28	0.12
2006	0.62	0.29	0.15
2007	0.63	0.31	0.14
2008	0.64	0.30	0.13
2009	0.63	0.30	0.13
2010	0.63	0.29	0.10
2011	0.66	0.30	0.11

Table 4. Efficiency rates in water, energy, and emissions of irrigated areas in Spain for the

332 2005–2011 period

333

The results of the FA showed that the observed variability of Spanish irrigated agriculture can be described by two main factors (Figure 4): 1) the size of the irrigated schemes; and 2) the specialization in the production of crops and use of certain water sources. These two factors explain

together 61.8% of the spatial and temporal variability observed.

338 Overall, the larger WF, EF, and CF are linked to the administrative regions with large irrigated schemes, that have experiencing the largest upgrades of their irrigation systems, and are highly 339 specialized in the production of permanent crops and the use of groundwater (Figure 4, top right 340 quadrant). These areas overlap with the southern half of Spain (i.e., the Andalusia and Castilla-La 341 Mancha regions). The central and northern parts of the country (the Castilla y Leon region) also have 342 large irrigated areas, albeit mostly devoted to the cultivation of non-permanent and low value crops 343 that rely heavily on the use of surface water (bottom right quadrant). In the eastern and southeastern 344 parts of Spain (the Murcia and Comunidad Valenciana regions), the irrigated area is moderate, but it 345 is also highly specialized in the production of permanent crops (mostly citrus trees) and high added-346 347 value vegetables, heavily reliant on the use of groundwater (top left quadrant). The relative energy costs here (kWh/m³) are among the highest in Spain. Other regions like Aragon, Extremadura, and 348 349 Cataluña are less specialized, and the irrigated area is smaller in comparison with the neighboring administrative regions (bottom left quadrant). Lastly, it is important to highlight that the changes in 350 351 irrigated areas and water demands observed between 2005 and 2011 have not altered the 352 geographical specialization pattern across the country.

353



Figure 4. Factorial analysis describing the typology of major irrigation regions (NUTS2) in Spain and its linkage to the water,
 energy, and carbon footprints. Note: grey areas in the map represent regions with little irrigation development (overall representing
 <6% of the national irrigated area).

359 **Discussion**

The results of this study show that the water demand of irrigated agriculture in Spain (Irr) dropped by 360 361 21% between 2005 and 2011, which is equivalent to a net savings of 5,391 hm³. The factors contributing to this reduction are diverse and cannot just be attributed to irrigation efficiency improvements. On the 362 363 one hand, the consumptive use of blue water (WF_{blue}) decreased by 2,700 hm³ mainly due to a reduction in harvested production (-1.1% with respect to 2005 levels) but, most importantly, due to the more 364 365 favorable climate conditions and crop choices in 2011 (higher P_{eff} and lower CWR), which reduced the relative blue water footprint of crops by 9% (4,830 m³/ha in 2005 and 4,380 m³/ha in 2011). This 366 confirms that, at the most, 50% of the achieved water savings (equivalent to 2,690 hm³) can potentially 367 be attributed to improvements in technical irrigation efficiency resulting from the replacement of the old 368 369 open air channel distribution infrastructure by pressurization pipe networks. Under this scenario, the 370 water savings resulting from improved efficiencies would have reached and actually surpassed the target of 2,500 hm³/year set in the PNR-2008 (MAPA, 2001a), and the Shock Plan 2006–2008 (MARM, 371 2006). 372

373 Nevertheless, this hypothesis that it is efficiency improvements that have led to the met the targeted 374 water savings cannot be confirmed. In fact, if the (dry) climate conditions of the year 2005 had prevailed 375 in 2011, this would have led to a 9% decrease in the Irr (equivalent to net reduction of -2,344 hm³). Under this scenario, net savings attributed to efficiency improvements would only have reached +1,800 376 377 hm³. These findings are in line with other studies (i.e., Birkenholtz, 2017; Lopez-Gunn et al., 2012; Molle et al., 2017; Pfeiffer and Lin, 2014); and where it has been proved that water use efficiency 378 379 policies have failed to achieve ambitious water savings targets and, in the worst case, to lead to an increase in water consumption. 380

Berbel et al. (2015) argued that water efficiency polices in areas suffering from over-allocation might 381 deliver real water savings as long as they are accompanied by a number of additional measures, 382 including: 1) a cap on the water extractions and on the further expansion of irrigated area; and 2) re-383 assignment of the water savings to the environment to release pressure on the system. In this respect, the 384 385 results of our analysis show that between 2005 and 2011 the irrigated area remained fairly stable. Only a slight increase of +0.3% was registered due to an expansion of irrigated areas in the Comunidad 386 387 Valenciana and Aragon regions, which was partly offset by the decrease experienced in some of the largest irrigated regions (Castilla-La Mancha and Castilla y Leon) (see Figure 4). Although the 388

establishment of caps on water extractions cannot be tested, the results of our study show that the shift

- in crop patterns has in fact had a positive impact by driving the progressive replacement of water-
- intensive herbaceous crops (sugar beet, cotton, and maize) by high-value and less water-intense woody
- 392 crops (particularly olive trees, citrus trees, and vineyards). According to our results, the average water
- demand per crop between 2005 and 2011 decreased by 14% (from 7,660 m³/ha to 6,610 m³/ha) and
- would have remained at 6% (from 7,660 m³/ha to 7,220 m³/ha) under constant climate conditions. The
- observed change in crop patterns confirms the results of Berbel et al. (2015) for southern Spain.
- However, it differs from other studies (i.e., Birkenholtz 2017 or Rodriguez-Diaz et al. 2011, 2012), who
- 397 found that shifts in crop patterns actually led to more water-intensive production.

The shift toward high-value crops has also come at the expense of an increasing use of groundwater. 398 399 This can be largely explained by the fact that groundwater is more resilient to climate variability (Calow 400 et al., 2010) and that it is the preferred source of water for farmers in order to avoid risks and secure the production of high-value crops. As Figure 4 shows, the highest use of groundwater for irrigation is 401 402 actually concentrated in the largest irrigated regions in Spain, namely, Andalusia, Castilla-La Mancha, Comunidad Valenciana, and Murcia, which are also the largest producers of cash crops. Some of these 403 regions support the cultivation and export of berries and fresh vegetables, with apparent water 404 productivities of $\in 8.5/m^3$ (Aldava et al., 2010) and $\in 7/m^3$ (Dumont et al., 2011), respectively. As pointed 405 406 out by De Stefano et al. (2014), groundwater in the period 2005–2008 generated at least 30% of the economic value of the national agricultural production of Spain, and this share is likely to keep growing 407 because of the prevailing shift in crop patterns. 408

409 The upgrading of irrigated infrastructures has also had implications from an energy and emissions 410 perspective. The overall decrease in the EF (-13%) is mainly related to the favorable climate conditions in 2011, which contributed to: 1) a decrease in the overall water demand (*Irr*); and 2) a reduction in the 411 412 groundwater table depth, and consequently groundwater pumping costs ($q_{pump GW}$), which represented at least 75% of the energy bill during the analyzed period. Our estimates for $q_{\text{pump GW}}$ during the period 413 analyzed show a slight decrease (0.59 kWh/m³ in 2005 and 0.48 kWh/m³ in 2011), and are slightly 414 higher with the average value of 0.39 kWh/m³ estimated by Corominas (2010). This difference might be 415 attributed to the fact that the q_{pump} GW calculation developed in this paper is sensitive to changes in the 416 water table depth, which helps gain a more accurate estimate of price changes between dry and wet 417 418 periods.

The literature on irrigation efficiency points to the fact that conversion into pressurized systems entails 419 higher energy costs, and this is often the main driving factor motivating farmers to ultimately save water 420 resources (Berbel et al., 2015; Rodriguez-Diaz et al., 2012; Soto-Garcia et al., 2013). Our study suggests 421 that despite the overall decrease in the *EF*, the average unitary costs (kWh/m^3) at the national level have 422 increased only moderately (Table 4). When looking separately at the unitary costs per irrigation system, 423 surface water–dependent systems (EF_{sw}) have seen cost increases of 4% (0.21 kWh/m³ to 0.22 kWh/m³), 424 whereas in groundwater-dependent systems the EF_{GW} has actually decreased by 7% (0.61 kWh/m³ to 425 0.57 kWh/m³). Once again, if the dry 2005 climate conditions had remained constant over the study 426 427 period, the EF_{SW} and the EF_{GW} would have increased by 5% and 15%, respectively. While our results confirm an upward trend in the energy intensity of irrigated systems, the observed increase is fairly 428 429 moderate compared with other assessments reporting energy costs increases above 70% (Jackson et al., 2010; Berbel et al., 2015). 430

From an emissions perspective, the reduction in the *CF* is greater than the overall *EF* decrease, and the dampening factor modulating this different behavior is the decreasing emission factor of electricity production from 0.46 kg CO₂ equiv./kWh in 2005 to 0.40 kg CO₂ equiv./kWh in 2011 (Figure 2c). This reduction is due to the mitigation policies implemented in the electricity sector with an increased penetration of renewable energies (11% in 2005 and 31% in 2011) in the electricity production mix of technologies in compliance with European Union targets (REE, 2006 and 2012).

437 The calculation of the CF relies on the assumption that electricity is the main source of energy for 438 irrigation. This assumption seems reasonable for the early 2000s, when at least 73% of the energy for irrigation was provided by electricity and only 27% came from diesel pumps (Corominas, 2010). 439 440 Published work on CFs in Spain (e.g., Bartzas et al., 2015; Martin-Gorriz et al., 2017), and in other countries such as India (Nelson et al., 2009; Shah, 2009) and China (Wang et al. 2012; Zou et al. 2015), 441 442 has shown the important impact of the energy source used for water pumping on the CF of irrigation. 443 Our results demonstrate that mitigation policies that reduce the CF of electricity generation have an 444 important effect on the sustainability of agricultural irrigation. GHG emissions from irrigation represent only a small share of the emissions from agriculture. The size of this share depends on many factors 445 including type of irrigation, source of water, and type of crop. Literature estimates range from an 8% 446 share in northern areas of Spain in extensive cereal crops using surface water and modern irrigation 447 448 systems (Abrahao et al., 2017), up to 35% in annual vegetable crops in the southeast of Spain using more than 50% of water from external transfers and almost 40% of groundwater. According to the latest 449

450 energy and climate plans (PNIEC, 2019), the trend in the electricity sector is toward an 83% reduction

451 in the carbon footprint of electricity generation in 2030 compared to 2005 and almost complete

452 decarbonization in 2050. These future reductions in global warming emissions from electricity will

453 enhance the observed downward tendency in the *CF* of Spanish irrigation.

454

455 **Conclusions**

This study shows that the irrigated sector in Spain has undergone an important transition in a relatively short period of time. From a less technology-based and heavily surface water-dependent agriculture it has moved toward being a modernized, more profitable and efficient one, that is also increasingly more reliant on groundwater.

460

From a resource-use perspective, the modernization of irrigated systems in Spain has contributed to 461 increasing the production efficiency and reducing the energy and carbon footprints, although the 462 efficiency gains are masked by a number of synergistic factors including favorable climate conditions 463 and changes in the energy mix. While these later changes in the energy mix are the result of an overall 464 transition toward a fully decarbonized sector by 2050 that will contribute to further increasing the 465 sustainability of irrigated agriculture, the changing climate conditions, and particularly the risk of higher 466 frequency of dry years, might compromise the positive outcomes of this water policy if not revised. The 467 results of this assessment pinpoint to the fact that effective water policies should combine investments in 468 469 irrigation infrastructures, with specific measures intended to set caps on the area that can be actually irrigated and/or the type of crops to be irrigated, particularly of water-intensive crops of low economic 470 471 value.

472 Acknowledgements

This research was supported by Fundacion Canal Isabel II through the project "Water, Food and Energy
Nexus in Spain" II [Grant number 140000CEI3006, 2014-2016] and by the Botin Foundation. The
authors would like to express their gratitude to Jorge Ruiz Fernandez and Matthew Witkin for their
support in the data collection and processing.

477

478 **References**

- 479 Abrahao, R., Carvalho, M., Causapé, J. 2017. Carbon and water footprint of irrigated corn and non-
- 480 irrigated wheat in Northeast Spain. Environmental Science and Pollution Research, 24: 5647-5653. DOI
- 481 10.1007/s11356-016-8322-5
- AEMET, Agencia Española de Meteorología. 2015. Monthly ET_o values from agro-meteorological
 stations across Spanish provinces (NUTS3), years 2005-2011. Dataset <u>http://www.aemet.es</u>. (accessed
 10.1.15).
- Aldaya, M. M., García-Novo, F., & Llamas, M. R. 2010. Incorporating the water footprint and
 environmental water requirements and policy: Reflections from the Doñana region. Papeles de Agua
 Virtual Series, n° 5. Botín Foundation.
- 488 Allen, R. G., Pruitt, W. O., Wright, J. L., Howell, T. A., Ventura, F., Snyder, R., ... & Smith, M. (2006).
- 489 A recommendation on standardized surface resistance for hourly calculation of reference ETo by the
- 490 FAO56 Penman-Monteith method. *Agricultural Water Management*, 81(1-2), 1-22.
- 491 <u>https://doi.org/10.1016/j.agwat.2005.03.007</u>
- 492 Bartzas, G., Zaharaki, D., Komnitsas, K. 2015. Life cycle assessment of open field and greenhouse
- 493 cultivation of lettuce and barley. *Information processing in agriculture*. 2: 191-207.
- 494 https://doi.org/10.1016/j.inpa.2015.10.001
- Berbel, J., Pedraza, V., Giannoccaro, G. 2013. The trajectory towards basin closure of a European river:
 Guadalquivir. *International Journal of River Basin Management*, 11(1):111-119.
 https://doi.org/10.1080/15715124.2013.768625
- Berbel, J., Gutiérrez-Martín, C., Rodríguez-Díaz, J.A., Camacho, E., Montesinos, P. 2015. Literature
- 499 review on rebound effect of water saving measures and analysis of a Spanish case study. *Water*
- 500 *Resources Management*, 29(3):663-678. DOI 10.1007/s11269-014-0839-0
- Birkenholtz, T. 2017. Assessing India's drip-irrigation boom: efficiency, climate change and
 groundwater policy. *Water International*, 42(6), 663-677.
- 503 https://doi.org/10.1080/02508060.2017.1351910
- 504 Brouwer, C. and Heibloem, M. 1986. Irrigation water management, Training manuals 3. Rome, Italy: Food and 505 Agriculture Organization.
- 506 Calow RC, MacDonald AM, Nicol AL and Robins NS. 2010. Ground Water Security and Drought in
- Africa: Linking Availability, Access, and Demand. *Ground Water*, 48(2):246–256. doi: 10.1111/j.17456584.2009.00558.x
- 509 CHD, Confederación Hidrográfica del Duero. 2015. River Basin Management Plan of the Spanish
- 510 Duero Basin. 2015-2021. Annex 5 Water demands. Government of Spain

- 511 CHE, Confederación Hidrográfica del Ebro. 2015. River Basin Management Plan of the Ebro Basin
- 512 2015-2021. Report. Government of Spain
- 513 CHG, Confederación Hidrográfica del Guadalquivir. 2015. River Basin Management Plan of the
- 514 Guadalquivir Basin 2015 2021. Annex 3: Water uses, demands and pressures. Government of Spain
- 515 Corominas, J. 2010. Agua y energía en el riego, en la época de la sostenibilidad. *Ingeniería del agua*,
 516 17(3): 219-233.
- Cosgrove, W. J., Loucks, D. P. 2015. Water management: Current and future challenges and research
 directions. *Water Resources Research*, 51(6), 4823-4839. https://doi.org/10.1002/2014WR016869
- 519 Daccache, A., Ciurana, J. S., Diaz, J. R., Knox, J. W. 2014. Water and energy footprint of irrigated
- agriculture in the Mediterranean region. *Environmental Research Letters*, 9(12), 124014.
 doi:10.1088/1748-9326/9/12/124014
- 522 De Stefano, L., and Llamas, M. R. (Eds.). 2012. Water, agriculture and the environment in Spain: can
 523 we square the circle?. CRC Press.
- Díaz, J. R., Urrestarazu, L. P., Poyato, E. C., Montesinos, P. 2012. Modernizing water distribution
 networks: Lessons from the Bembézar MD irrigation district, Spain. *Outlook on Agriculture*, 41(4), 229236. https://doi.org/10.5367/oa.2012.0105
- 527 Dumont, A., Mayor, B., López-Gunn, E. 2013. Is the rebound effect or Jevons paradox a useful concept
 528 for better management of water resources? Insights from the Irrigation Modernisation Process in
- 529 Spain. *Aquatic procedia*, 1, 64-76. https://doi.org/10.1016/j.aqpro.2013.07.006
- 530
- 531 Dumont, A., López-Gunn, E., & Llamas, M. R. 2011. La huella hídrica extendida de las aguas
- subterráneas en el Campo de Dalías (Almería, España) [The extended water footprint of Campo de
 Dalías' groundwater]. Congreso Ibérico de Aguas Subterráneas: desafíos de la gestión para el siglo XXI.
- 534 AIG-GE. Zaragoza.
- 535 EUROSTAT, European Statistical Office. 2014. Annual freshwater abstraction by source and sector.

Available at: <u>http://appsso.eurostat.ec.europa.eu/nui/show.do?dataset=env_wat_abs&lang=en</u>(Accessed
 24.07.2017)

- 538
- 539 Frischknecht R., Jungbluth N., Althaus H.-J., Doka G., Dones R., Heck T., Hellweg S., Hischier R.,
- 540 Nemecek T., Rebitzer G. and Spielmann M., 2005. The ecoinvent database: Overview and
- 541 methodological framework, *International Journal of Life Cycle Assessment* 10, 3–9. DOI:
- 542 http://dx.doi.org/10.1065/lca2004.10.181.1
- 543 Garrido, A., M.R. Llamas, C. Varela-Ortega, P. Novo, R. Rodríguez-Casado, M.M. Aldaya. 2010.
- 544 Water Footprint and Virtual Water Trade in Spain. Springer, Nueva York. 189 pp

- Gleick, P. H. 2003. Global freshwater resources: soft-path solutions for the 21st century. *Science*, 302 (5650): 1524-1528. DOI: 10.1126/science.1089967
- 547 Gleick, P.H. 2014. The World's Water: The Biennial Report on Freshwater Resources. Island Press,
 548 Washington, DC.
- Gómez, C.M., Pérez-Blanco, C.D. 2014. Simple myths and basic maths about greening irrigation. *Water Resources Management*, 28: 4035. DOI 10.1007/s11269-014-0725-9
- 551 Gómez, C.M., Gutiérrez, C. 2011. Enhancing Irrigation Efficiency but Increasing Water Use: The
- 552 Jevons' Paradox Paper prepared for presentation at the EAAE 2011 Congress Change and Uncertainty
- 553 Challenges for Agriculture, Food and Natural Resources August 30 to September 2, 2011ETH Zurich,
- 554 Zurich, Switzerland.
- Grafton, R. Q., Williams, J., Perry, C. J., Molle, F., Ringler, C., Steduto, P., ... & Allen, R. G. 2018. The
 paradox of irrigation efficiency. *Science*, *361*(6404), 748-750. DOI: 10.1126/science.aat9314
- Hoekstra, A.Y., Chapagain, A.K., Aldaya, M.M., Mekonnen, M.M. 2011. The water footprint
 assessment manual: Setting the global standard, Earthscan, London, UK.
- Hoekstra, A.Y., Mekonnen, M.M. 2012. The water footprint of humanity. *Proceedings of the National Academy of Sciences*, 109(9). https://doi.org/10.1073/pnas.1109936109
- INE, Instituto Nacional de Estadística. 2012.Survey on annual water use in the agricultural sector: Data
 on availability and source, period 2005- 2011.
- http://www.ine.es/dyngs/INEbase/es/categoria.htm?c=Estadistica_P&cid=1254735976602 (accessed
 8.12.2015).
- 565 Jackson TM, Khan S, Hafeez M .2010. A comparative analysis of water application and energy
- consumption at the irrigated field level. *Agricultural Water Management* 97:1477–1485
 https://doi.org/10.1016/j.agwat.2010.04.013
- 568 Karimi, P., Qureshi, A. S., Bahramloo, R., Molden, D. 2012. Reducing carbon emissions through
- improved irrigation and groundwater management: A case study from Iran. *Agricultural Water Management*, 108, 52-60. https://doi.org/10.1016/j.agwat.2011.09.001
- 571 Kuriqi, A., Pinheiro, A., Sordo-Ward, A., & Garrote, L. (2017). Trade-off between environmental flow 572 policy and run-of-river hydropower generation in Mediterranean climate. *Eur. Water*, *60*, 123-130. DOI:
- 573 10.13140/RG.2.2.23257.21608
- 574 Kuriqi, A., Pinheiro, A. N., Sordo-Ward, A., & Garrote, L. (2019). Influence of hydrologically based
- environmental flow methods on flow alteration and energy production in a run-of-river hydropower
- 576 plant. Journal of Cleaner Production 232:1028-1042. <u>https://doi.org/10.1016/j.jclepro.2019.05.358</u>

- 577 Lecina, S., Isidoro, D., Playán E., Aragüés, R. 2010. Irrigation modernization and water conservation in
- 578 Spain: The case of Riegos del Alto Aragón. Agricultural Water Management, 97 (10): 1663-1675
- 579 https://doi.org/10.1016/j.agwat.2010.05.023
- Llamas, M. R., Martínez-Santos, P. 2005. Intensive groundwater use: silent revolution and potential
 source of social conflicts. *Journal of Water Resources Planning and Management*, 131(5), 337-341.
 https://doi.org/10.1061/(ASCE)0733-9496(2005)131:5(337)
- 583 Lopez-Gunn, E., Zorrilla, P., Prieto, F., & Llamas, M. R. 2012. Lost in translation? Water efficiency in
- 584 Spanish agriculture. *Agricultural Water Management*, *108*, 83-95.
- 585 https://doi.org/10.1016/j.agwat.2012.01.005
- Lorite, I.J., Mateos, L., Fereres, E. 2004. Evaluating irrigation performance in a Mediterranean
- environment. II. Variability among crops and farmers. *Irrigation Science*, 23:85–92.
- 588 http://doi.org/10.1007/s00271-004-0096-8

589 MAGRAMA, Ministry of Agriculture, Food and the Environment. 2015a Crop Annual Surveys series

- 590 2005-2011. Available at: http://www.magrama.gob.es/es/estadistica/temas/publicaciones/anuario-de-
- 591 estadistica/ (accessed 12.12.2016).
- 592 MAGRAMA, Ministry of Agriculture, Food and the Environment. 2015b. Survey on agricultural areas 593 and yields, series 2005-2011. Available at: http://www.
- magrama.gob.es/es/estadistica/temas/publicaciones/anuario-de-estadistica/ (accessed 12.12. 2016).
- 595 MAGRAMA, Ministry of Agriculture, Food and the Environment. 2015c. Red Oficial de Seguimiento
- del Estado Cuantitativo: Red piezométricos. Available at:
- 597 http://sig.magrama.es/recursossub/visor.html?herramienta=Piezometros (accessed 12.12. 2016).
- MAPA-Ministry of Food, Agriculture, and Fishery. 2001a. Plan Nacional de Regadios. Horizonte 2008
 [National Irrigation Plan. Horizon 2008]. Direccion General de Desarrollo Rural, Madrid, Spain (in
 Spanish)
- 601 MAPA- Ministry of Food, Agriculture, and Fishery. 2001b. Calendario de siembra, recolección y
- comercialización, años 1996-1998. Ministerio de Agricultura, Pesca y Alimentación, Madrid, España,
 603 656pp. (in Spanish)
- MAPAMA, Ministry of Agriculture, Fisheries, Food, and the Environment, 2017. Comunicación al
 secretariado de la convención marco de NNUU sobre cambio climático. Inventario nacional de
- 606 emisiones de gases de efecto invernadero 1990 2015. Edición 2017. Available at:
- 607 <u>http://www.mapama.gob.es/es/calidad-y-evaluacion-ambiental/temas/sistema-espanol-de-inventario-sei-</u>
- 608 /<u>nir_2017_abril_tcm7-453259.pdf</u>. (accessed 12.07. 2017).

- 609 MARM-Ministry of Environment, Rural areas and Marine Environment, 2006. Plan de choque de
- modernizacion de regadios 2006-2008 [Irrigation modernization shock plan, 2006-2008]. Ministerio de
 Medio Ambiente, Medio Rural y Marino, Madrid, Spain (in Spanish).
- 612 Martin-Gorriz, B., Soto-García, M., Martínez-Álvarez, 2017. Energy and greenhouse-gas emissions in
- 613 irrigated agriculture of SE(southeast) Spain. Effects of alternative water supply scenarios. *Energy*, 77:
- 614 478-488. https://doi.org/10.1016/j.energy.2014.09.031
- Martínez-Paz, J. M., Gomariz-Castillo, F., & Pellicer-Martínez, F. (2018). Appraisal of the water
- footprint of irrigated agriculture in a semi-arid area: The Segura River Basin. *PloS one*, *13*(11),
 e0206852.
- 618 Mehran, A., AghaKouchak, A., Nakhjiri, N., Stewardson, M. J., Peel, M. C., Phillips, T. J., ... &
- 619 Ravalico, J. K. .2017. Compounding impacts of human-induced water stress and climate change on
- 620 water availability. *Scientific reports*, 7(1), 6282. DOI:10.1038/s41598-017-06765-0
- Molden, D., K. Frenken, R. Barker, C. DeFraiture, B. Mati, M. Svendsen, C. Sadoff, M. Finlayson, S.
- Atapattu, M. Giordano, A. Inocencio, M. Lannerstad, N. Manning, F. Molle, B. Smedema, D. Vallee.

623 2007. Trends in water and agricultural development. In: D. Molden (ed). Water for food, water for life: a

- 624 comprehensive assessment of water management in agriculture. Earthscan, London, UK and
- 625 International Water Management Institute, Colombo, Sri Lanka. pp 57–89.
- 626 Molle, F., and Tanouti, O. 2017. Squaring the circle: Agricultural intensification vs. water conservation
- 627 in Morocco. *Agricultural Water Management*, *192*, 170-179.
- 628 https://doi.org/10.1016/j.agwat.2017.07.009
- 629 Nelson, G.C. and Robertson, R. 2008. Personal Communication
- 630 Nelson, G.C., Robertson, R., Msangi, S., Zhu, T., Liao, X., Jawajar, P. 2009. Greenhouse Gas
- 631 Mitigation. Issues for Indian Agriculture. IFPRI Discussion Paper 00900.
- OECD, The Organization for Economic Co-operation and Development. 2011. Water governance in
- OECD countries: A Multi-Level approach, OECD Studies on Water, OECD Publishing, Paris. DOI:
 10.1787/9789264119284-en
- PNIEC, Plan Nacional Integrado de Energía y Clima, 2019. Plan 2021-2030. Ministerio de Transición
 Ecológica. <u>https://www.idae.es/informacion-y-publicaciones/plan-nacional-integrado-de-energia-y-</u>
 <u>clima-pniec-2021-2030</u>
- 638 Pfeiffer, L., Lin, C. Y. C. 2014. Does efficient irrigation technology lead to reduced groundwater
- extraction? Empirical evidence. *Journal of Environmental Economics and Management*, 67(2): 189-208.
- 640 Playán, E., Mateos, L. 2006. Modernization and optimization of irrigation systems to increase water
- 641 productivity. Agricultural Water Management, 80: 100–116. https://doi.org/10.1016/j.jeem.2013.12.002

- 642 REE, Red Electrica Española. 2006. Informe del sistema eléctrico español 2005.
- 643 http://www.ree.es/es/publicaciones/sistema-electrico-espanol/informe-anual. (accessed 2.04.2018)
- 644 REE, Red Electrica Española. 2012. Informe del sistema eléctrico español 2011.
- 645 http://www.ree.es/es/publicaciones/sistema-electrico-espanol/informe-anual. (accessed 2.04.2018)
- 646 Rodríguez-Díaz, J. A., Pérez-Urrestarazu, L., Camacho-Poyato, E., Montesinos, P. 2011. The paradox of
- 647 irrigation scheme modernization: more efficient water use linked to higher energy demand. *Spanish*
- 648 *Journal of Agricultural Research*, 9(4): 1000-1008. DOI: 10.5424/sjar/20110904-492-10
- 649 Rodríguez Díaz, J.A., Pérez Urrestarazu, L., Camacho Poyato, E., Montesinos, P., 2012. Modernizing
- 650 water distribution networks lessons from the Bembézar MD irrigation district, Spain. *Outlook*
- 651 *Agriculture* 41(4): 229–236. <u>https://doi.org/10.5367/oa.2012.0105</u>
- Scheierling, S. M., Young, R. A., Cardon, G. E. 2006. Public subsidies for water-conserving irrigation
 investments: Hydrologic, agronomic, and economic assessment. *Water Resources Research*, 42(3).
- Shah, T. 2009. Climate change and groundwater: India's opportunities for mitigation and adaptation.
 Environment Research Letters 4 035005 (13 pp). doi:10.1088/1748-9326/4/3/035005
- 656 Soto-García, M., Martin-Gorriz, B., García-Bastida, P. A., Alcon, F., Martínez-Alvarez, V. 2013.
- Energy consumption for crop irrigation in a semiarid climate (south-eastern Spain). *Energy*, 55: 1084 1093. https://doi.org/10.1016/j.energy.2013.03.034
- 659 Veldkamp, T. I. E., Wada, Y., Aerts, J. C. J. H., Döll, P., Gosling, S. N., Liu, J., ... & Satoh, Y. 2017.
- 660 Water scarcity hotspots travel downstream due to human interventions in the 20th and 21st
- century. *Nature communications*, *8*, 15697. DOI: 10.1038/ncomms15697
- 662 Wang, J., Rothausen, S.G.S.A, Conway, D., Zhang, L., Xiong, W., Holman, I.P., Li, Y. 2012. China's
- water-energy nexus: greenhouse-gas emissions from groundwater use for agriculture. *Environment Research Letters* 7 014035. doi:10.1088/1748-9326/7/1/014035
- 665 Ward, F.A., Pulido-Velazquez, M. 2008. Water conservation in irrigation can increase water
- use. *Proceedings of the National Academy of Sciences*, 105(47): 18215-18220.
- 667 https://doi.org/10.1073/pnas.0805554105
- WWAP, United Nations World Water Assessment Programme, 2016. The United Nations World Water
 Development Report 2016: Water and Jobs. Paris, UNESCO.
- 670 Zou X., Li, Y., Li, K., Cremades, R., Gao, Q., Wan, Y., Qin, X. 2015. Greenhouse gas emissions from
- agricultural irrigation in China. *Mitigation and Adaptation Strategies for Global Change*, 20: 295-315.
- 672 DOI 10.1007/s11027-013-